Appendix A Monitoring Equipment Photographs

Photograph A1
Groundwater Monitoring Piezometer Installation at a Groundwater Monitoring Location Using Geoprobe
Drilling Rig



Note: New groundwater piezometers were installed at Sites 007, 004, and 086.

Photograph A2
Groundwater Monitoring Piezometer Well Development Via Surging, Bailing, and/or Pumping

Photograph A3
Completed Groundwater Monitoring Piezometer with Cover Removed Showing In-Situ Rugged Troll 200 Data
Logger Cable and Coupler



Photograph A4
Completed Groundwater Monitoring Piezometer with Cover Installed




Photograph A5
Perforated Galvanized Steel Pipe and Drive Point Used to Construct the Stilling Wells at the River Monitoring Locations and Oxbow Pond Monitoring Locations



Photograph A6
Typical Stilling Well Installation at a River Monitoring Location Along the Chehalis River



Note: A monitoring location benchmark is visible in the foreground.



Photograph A8


Data Collection at a River Monitoring Location



Note: Data logger cable from stilling well is pulled out of well riser and connected to a Rugged Reader portable field computer. Survey equipment for manually measuring water elevation in river is shown at the right.

Photograph A9

Typical Monitoring Setup at an Oxbow Monitoring Location



Note: Two Oxbow Monitoring Locations were installed at each monitoring site.

Photograph A10
Typical Oxbow Monitoring Location Configuration When Surface Water Is Present



Photograph A11
Typical Installation of an in-Situ BaroTroll Barometric Pressure Data Logger



Note: These were installed at Sites 007, 004, 068, and 086.

Photograph A12
River Flow Measurement Using an Acoustic Doppler Current Profiler Mounted on a Small Boat



Appendix B Groundwater Monitoring Well Logs

The Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report

Site 007 - Groundwater Well Log

Please print, sign and return to the Department of Ecology

	CE PROTECTION		CURRENT	Notice of Ir	ntent No. <u>RE12487</u>		
•			ő.		ll ("x in box) ce Protection h Soil Boring		
_	STALLATION Notice of Inten	t Number:	Property Owner Weyerhauser Pe Ell Tree Farm				
			Site Address 1098 Muller Rd.				
Consulting Firm Anchor QEA, LLC Unique Ecology Well IDTag No. BHV-137			City Pe Ell County Lewis				
			Location <u>SE</u> 1/4-1/4 <u>NE</u> 1/4 Sec 4 Twn 12N R 5W				
WELL CONST	RUCTION CERTIFICATIO	N: I constructed and/or	EWM or WWM				
accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported bove are true to my best knowledge and belief.			Lat/Long (s, t, r Lat Deg Min Sec still REQUIRED) Long Deg Min Sec				
☑ Driller ☐ Eng	ineer Trainee		Tax Parcel No.016431000000				
Name (Print Last, F	First Name) King, Kyle or /Trainee Signatu			12-5-	Static Level 10.3'		
Oriller or Train	ee License No. 3220		Work/Decommission	on Start Date 3/	/4/2016		
f trainee, licer	nsed driller's Signature and	License Number:	Work/Decommission	n Completed I	Date 3/4/2016		
	1000						
Cor	nstruction Design	Well I	Data	Fo	ormation Description		
0 – 1 ft	8" flush monument	5004-GML			Silty and Some Gravel		
	set in concrete	2" piezometer well	to 21 ft.	8.5 – 21 ft	Sandy Gravel		
0.5 – 11 ft	2" PVC riser	Borehole diameter: 4"			96.		
11 – 21 ft	2" PVC prepack screen threaded, 0.001 slot	8" flush monument:					
		Bentonite Seal: 1 – 10 ft.			9		
		Filter Pack: 10 – 21	ft.	(T			
		1	l				
			A#	3			
		-		i	RECEIVED		
					i p		
				<u> </u>	OCT 25 2016		
				V	VA State Department of Ecology (SWRO)		

The Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report

Site 004 - Groundwater Well Log

Please print, sign and return to the Department of Ecology

	E PROTECTION '		CURRENT	Notice of Inte	nt No. <u>RE12486</u>		
(SUBMIT ONE WELL REPORT PER WELL INSTALLED) Construction/Decommission ("x" in box) 303-16-1192 Construction			Type of Well ("x in box) ☐ Resource Protection				
Decommissio	n		8.	Geotech So	oil Boring		
ORIGINAL INSTA	ALLATION Notice of Intent	Number:	Property Owner Thomas Christin				
				Site Address 602-798 Meskill Rd.			
Consulting Firm A	Anchor QEA, LLC		City Chehalis County Lewis				
Unique Ecology V	Well IDTag No. <u>BHV-136</u>		Location <u>SE</u> 1/4-1/4 <u>SW</u> 1/4 Sec <u>3</u> Twn <u>13N</u> R <u>4W</u>				
WELL CONSTRI	WELL CONSTRUCTION CERTIFICATION: 1 constructed and/or accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.			EWM or WWM			
Washington well const				Lat Deg	_ Min Sec		
	-		still REQUIRED)		MinSec		
☑ Driller ☐ Engined Name (Print Last, First		_ 11					
Driller/Engineer /	Trainee Signature		Cased or Uncased I	Diameter 2"	Static Level 12'		
Driller or Trainee	License No. 3220		Work/Decommission	on Start Date 3/2/2	2016		
If trainee, license	d driller's Signature and	License Number:	Work/Decommission	on Completed Date	e <u>3/3/2016</u>		
Const	ruction Design	Well	Data ·	Form	ation Description		
0 – 1 ft	8" flush monument	5007-GML		0 - 8 ft Silty	y Gravel		
	set in concrete	2" piezometer well	to 23 ft.	8 – 23 ft Sar	ndy Gravel		
0.5 – 17.5 ft	2" PVC riser	Borehole diameter: 4")			
17.5 – 22.5 ft	2" PVC prepack screen threaded, 0.001 slot	8" flush monument:	0 – 1 ft.				
ţ;		Bentonite Seal: 1 – 16.5 ft.					
		Filter Pack: 16.5 –	23 ft.				
				•			
				ß			
	(8	2	•				
Q1				li .			
			WE WE				
			V)		kj.		
			ne sa	REC	SEIVED		
				† oct	2 5 2018		
	و المراجعة	stru-		WA State	Department		

Site 068 - Groundwater Well Log HOLT DRILLING, INC.

Resource Protection Well Report

Well Identification # MW-3/Tag # ABO432 County Lewis , SE 1/4 SE Drilling Method 4" ASA Section 36 T. 13N R. 3W	113177	01		, , , , , , , , , , , , , , , , , , ,		
Drilling Method H" ASA Section 36 T. 13N R. 3W Street Address Farm Fields off of Hury 6 Start Card R55192 Consulting Firm Kebinson & Noble MONUMENT TYPE 6"Strick-up 2.5" Above 6 rand CONCRETE SURFACE SEAL 1.5 ft. PVC BLANK 2 "x19.5" BACKFILL 13.5 ft. TYPE-Bentonite PVC SCREEN 2 x 10 SLOT SIZE O20 TYPE PUC GRAVEL PACK 12 ft. MATERIAL 10/20 Silica REMARKS 3-3" x7" Steel BOllards placed & concerted around monument	Project Name Chenous Paci	Street Address Farm Fields off of 17wy 6				
Street Address Farm Fields off of Huy 6 Start Card R55192 Consulting Firm Rebinson & Mobile AS-BUILT WELL DATA MONUMENT TYPE 6"Stick-up 2.5' Above 6 round CONCRETE SURFACE SEAL 1.5 ft. PVC BLANK 2 "x19.5" BACKFILL 13.5 ft. TYPE Bentonite PVC SCREEN 2 x 10 representation of Ecology TYPE PUC GRAVEL PACK 12 ft. MATERIAL 10/20 Silica REMARKS 3-3" v7' Steel BOllards placed a concerted around monument						
Start Card R55192 Consulting Firm Rebinson & Noble AS-BUILT WELL DATA FORMATION DESCRIPTION MONUMENT TYPE 6"Strick up 2.5" Above Ground CONCRETE SURFACE SEAL 1.5 ft. PVC BLANK 2 "x19.5" BACKFILL 13.5 ft. TYPE Benstenite PVC SCREEN 2 "x 10" SLOT SIZE O20 TYPE PUC GRAVEL PACK 12 ft. MATERIAL 10/20 Silica RECEIVED Mashington State Department of Ecology ft. REMARKS 3-3" x7" Steel bollards placed a concerted around monument	Drilling Method 4" #5#					
Consulting Firm Robinson & Noble AS-BUILT WELL DATA FORMATION DESCRIPTION MONUMENT TYPE 6"Strick-up/2.5' Above broand CONCRETE SURFACE SEAL 1.5 ft. PVC BLANK 2 "x19.5" BACKFILL 13.5 ft. TYPE: Bentonite FORMATION DESCRIPTION 0 20 ft. Lt Brn. Si Hy Fine Sand 20 27 ft. Brn. Hed. Sand "/ Scattered Sm Gravels FORMATION DESCRIPTION RECEIVED NOVIT 4 2001 Washington State Department of Ecology ft. REMARKS 3-3" v 71 Steel Bollards placed a concerted around monument	•					
AS-BUILT WELL DATA FORMATION DESCRIPTION MONUMENT TYPE 6"Stick-up / 2.5' Above 6 round CONCRETE SURFACE SEAL 1.5 ft. PVC BLANK 2 'x19.5' BACKFILL 13.5 ft. TYPE: Bentonite PVC SCREEN 2 'x 10 ' SLOT SIZE , 020 TYPE PUC GRAVEL PACK 12 ft. MATERIAL 10/20 Silica MATERIAL 10/20 Silica REMARKS 3-3" V7' Steel bollards placed a concented around monument	License #_2442		Start Card <u>R55i92</u>			
MONUMENT TYPE 6"Stick-up /2.5" Above Ground CONCRETE SURFACE SEAL 1.5 pvc BLANK 2 "x19.5" BACKFILL 13.5 TYPE: Bentenite PVC SCREEN 2"x 10" SLOT SIZE 1026 TYPE PUC GRAVEL PACK 12 ft. MATERIAL 10/20 Silica RECEIVED Washington State Department of Ecology ft. REMARKS 3-3" x7" Steel bollards placed a concreted arrund monument	Г	Consulting Firm Kobinsun & Noble				
6"Stick-up/2.5" Above Grand CONCRETE SURFACE SEAL 1.5 pvc BLANK 2 "x19.5" BACKFILL 13.5 TYPE Bentenite PVC SCREEN 2 "x 10" SLOT SIZE , 020 TYPE PUC GRAVEL PACK 12 ft. MATERIAL 10/20 Silica RECEIVED Washington State Department of Ecology ft. REMARKS 3-3" v7" Stev bollards placed a concretad arrund monument	AS-BUILT	WELL DATA		FORMATION DESCRIPTION		
around monument		6"Stick-up/2.5" CONCRETE SURFACE I.5 ft. PVC BLANK 2 " BACKFILL 13.5 TYPE-Benton PVC SCREEN 2 " SLOT SIZE 02 TYPE PUC GRAVEL PACK 1	x19.5, ft. 1+c x 10, 20, 2 ft.	20 - 27 ft Brn. Hed. Sand Sm Gravels RECI NOV Washin Departmen	EIVED † 4 2001 gton State nt of Ecology	
		WELL DEPTH_ <u>27</u>	, <u>a</u>	bullards placed	a concreted	
<u> </u>						

D15332 FDB/D41029 EPS

The Department of Ecology does NOT Warranty the Data and/or the Information on this Well Report


Site 086 - Groundwater Well Log


Please print, sign and return to the Department of Ecology


	RCE PROTECTION				ent No. <u>RE13028</u>	
(SUBMIT ONE WELL REPORT PER WELL INSTALLED) Construction/Decommission ("x" in box) 303-16-1192 □ Construction □ Decommission			Type of Well ("x in box) ☐ Resource Protection ☐ Geotech Soil Boring			
ORIGINAL INSTALLATION Notice of Intent Number:			Property Owner Washington Dept. of Fish and Wildlife			
			Site Address 5993 US Hwy. 12			
	rnn Anchor QEA, LLC		City Oakville County Grays Harbor			
Unique Ecolo	ogy Well IDTag No. <u>B HV143</u>		Location <u>SW</u> 1/4-1/4 <u>SW</u> 1/4 Sec <u>34</u> Twn <u>17N</u> R <u>5W</u>			
WELL CONSTRUCTION CERTIFICATION: 1 constructed and/or accept responsibility for construction of this well, and its compliance with all Washington well construction standards. Materials used and the information reported above are true to my best knowledge and belief.			EWM or WWM Lat/Long (s, t, r Lat Deg Min Sec Long Deg Min Sec Long Deg Min Sec			
☑ Driller □ Fr	ngineer Trainee		Tax Parcel No.0224			
Name (Print Last	, First Name) King, Kyle			:=:	Static Level 10 . 68 '	
	eer /Trainee Signature inee License No. 3220					
	nice Electise 140. <u>5220</u>		Work/Decommission			
f trainee, lic	ensed driller's Signature and	License Number:	Work/Decommission	on Completed Dat	te <u>6/28/2016</u>	
C	onstruction Design	Well I	Data Formation Description			
0 – 2 ft	8" flush monument	5086-GML		0 – 10 ft	Silt	
	set in concrete			10 – 13.5 ft	Silty Sand	
0 – 15 ft	2" PVC riser	2" piezometer well to 25 ft.		13.5 – 25 ft	Gray Sand/River Rock	
0 – 1511		Borehole diameter:	4 "	13.3 – 23 11	Gray Sand/Niver Nock	
15 – 25 ft	2" PVC prepack	Borenoic diameter.	· .		*	
	screen threaded,	8" flush monument:	0 – 1 ft.	L		
	0.001 slot		10.50		SI .	
		Bentonite Seal: 2 –	12.5 ft.			
		Filter Pack: 12.5 - 2	25 ft.			
		₽	*	35		
				11		
				8 %	×	
š		W 31				
		in in		i.		
12				RECE	NER	
				NECE	1 V L L	
			OCT 2 5 2010		2010	
			£R	WA State De		
-				of Ecology	(SWRO)	


PAGE


Appendix C Water Elevation Graphs














































Appendix D Temperature Graphs


























Appendix E Chehalis River Gaining and Losing Reach Map




Figure 4. Discharge gains and losses in reaches along the Chehalis River, Washington.

Appendix F Acoustic Doppler Current Profiler Flow Survey Results

ACOUSTIC DOPPLER CURRENT PROFILER FLOW SURVEY RESULTS

Table F-1
Chehalis River Acoustic Doppler Current Profiler Discharge Measurements and Water Level Elevations on April 24, 2017

											WATER		ADNA GAGE (NO. 12021800)			
LOCATION	TRANSECT ID	DATE	TIME	TOTAL DISCHARGE (CFS)	TOTAL DISCHARGE DIFFERENCE FROM AVERAGE	AVERAGE DISCHARGE (CFS)	FLOW SPEED (FEET PER SECOND)	FLOW SPEED DIFFERENCE FROM AVERAGE	AVERAGE FLOW SPEED (FEET PER SECOND)	TIME	LEVEL AT SITES 020 AND 068 RML2 (UPSTREAM) FEET (NAVD88)	WATER LEVEL AT SITES 020 AND 068 RML1 (DOWNSTREAM) FEET (NAVD88)	WATER LEVEL ELEVATION FEET (NAVD88)*	TOTAL DISCHARGE (CFS)	AVERAGE DISCHARGE (CFS)	AVERAGE DISCHARGE DIFFERENCE BETWEEN TRANSECTS AND GAGE
Central	2003	4/24/2017	11:23	1,851	101%	1,830	2.21	99%	2.24	11:30	161.51	161.37	196.10	1,800	1,817	101%
transects	2004		11:27	1,803	99%		2.24	100%								
between	2005		11:32	1,855	101%		2.33	104%								
Sites 020	2006		11:37	1,774	97%		2.22	99%								
and 068	2007] [11:41	1,881	103%		2.29	102%		11:45	161.53	161.38	196.13	1,820		
	2008] [11:46	1,824	100%		2.21	98%								
	2010		11:55	1,823	100%		2.21	98%		12:00	161.56	161.36	196.14	1,830		
Downstream	4000	4/24/2017	12:38	1,907	100%	1,905	2.30	99%	2.33	12:45	161.68	161.56	196.14	1,830	1,857	103%
transects	4001		12:43	1,859	98%		2.48	106%								
between	4002		12:47	1,928	101%		2.33	100%								
Sites 020	4003		12:55	1,876	98%		2.28	98%		13:00	161.72	161.59	196.15	1,840		
and 068	4004] [13:00	1,937	102%		2.29	98%								
	4006		13:08	1,925	101%	<u>, </u>	2.31	99%		13:15	161.75	161.57	196.21	1,900		
Washington	5000	4/24/2017	15:38	2,119	102%	2,084	2.22	105%	2.12	15:45	162.30	161.89	196.41	2,080	2,120	98%
Route 603	5003		15:55	2,012	97%		2.05	97%		16:00	162.35	161.90	196.44	2,110		
bridge	5004		15:58	2,143	103%		2.05	97%								
transects	5006		16:05	2,046	98%		2.09	99%								
	5007		16:09	2,061	99%		2.22	105%		16:15	162.41	161.97	196.50	2,170		
	5008	1	16:13	2,123	102%		2.08	98%								

Notes:

^{*}Conversion from the gage's native datum (NVGD29) to North American Vertical Datum of 1988 (NAVD88) is +3.40 feet: https://www.ngs.noaa.gov/cgi-bin/VERTCON/vert_con.prl